

569GL-50NP/H/Y

(HDMI output optional)

569GL-50NP/HO/Y



5"

LCD Video Camera Monitor with

HDMI & YPbPr Input

- ▶ Specific LCD Monitor by LILLIPUT Uses for Full HD Video Camera Seizing much more clear world
- ▶ Application for Full HD Video Camera in CCTV Monitoring and Making Movies

- HDMI & YPbPr Input, to connect with Full HD Video Camera
- LCD 16:9 Aspect Ratio, max 1920×1080 pixels
- High Brightness/Contrast & Dizzy-proof monitor with sun shade, to see clearly under sunshine.
- Shooting view aperture, RGB monochromatic display, 16:9 / 4:3 aspect ratio switch, underscan/overscan switch, HDMI & Video output.
- DC 6-24V wide range voltage
- 4 user-definable function buttons (F1, F2, F3 & F4)
- High capacity rechargeable Li-ion battery, make power cables free.



MODEL:DU21



MODEL:QM91D



MODEL:F-970

DV Battery Mount Plate

Model DU21 for battery of Panasonic DV: NV-GS/PV-GS/DZ-MV/GS/H28/H258/H288GK series, comply with Panasonic battery DU06/VBD140/SANYODZhs301sw/Hitachi DZ-HS303SW/BZ-BP14S/DZ3200/BP07W

Model QM91D for battery of SONY DV: DSCR1/F/S/MVCCD/E/HC15E/HC1E/AE1u/DCRTRV828/E/CCD-TRV116/DCR-DVD/PS105K/300K/10P/1E series

Model F970 for battery of SONY DV: DCR-TRV series, DCR-TRV E series, VX2100E PD P series, GV-A700, GV-D800 FD/CCD-SC/TR3/FX1E/HVR-AIC, HDR-FX1000E, HVR-Z1C, HVR-V1C, FX7E F330

Specifications

Panel Size:	5" TFT LCD (16:9)
Resolution:	800×480, up to 1920×1080
Brightness:	400cd/m ²
Contrast:	600:1
Viewing Angle:	150°/ 130° (H/V)
Input Voltage:	DC 6-24V
Input Signal:	HDMI, YPbPr, AV
Current:	450mA
Standby Current:	50mA
Power Consumption:	5.4W
Audio Output:	≥250mW
Earphone Slot:	×1 (front)
Size (LWD):	151×116×39.5mm/98.1mm (with sun shade)
Weight:	316g / 386g (with sun shade)

Accessories

Sun shade	1piece
Battery Plate (DU21/QM91D/F970)	2piece
DC adapter	1piece
Manual	1copy
Bracket	1piece
Li-ion battery (optional)	1piece
HDMI to mini HDMI cable (optional)	1piece
Shoe mount (for camera only) (optional)	1piece

