

7"

LCD Monitor with HDMI & YPbPr Input 668GL-70NP/H/Y

Application for Full HD Video Camera in
CCTV Monitoring and Making Movies

LCD 16:9 Aspect Ratio

HDMI & YPbPr Input

Max 1920×1080 pixels



Shoe mount



PARAMETER

Panel Size	7" TFT LCD (16:9)
Resolution	800×480, up to 1920×1080
Brightness	450cd/m ² (optional: 250cd/m ²)
Contrast	500:1
Viewing Angle	120°/ 140°(H/V)
Input Voltage	DC 12V
Input Signal	HDMI, YPbPr, AV
Battery	2200mAh/7.4V (built-in)
Current	650mA (1.2A when charging)
Standby Current	≤50mA
Power Consumption	≤8W
Input Resistance	75Ω
Input Frequency	H/30-60KHz, V/60-75Hz
Audio Output	≥250mW
Speaker	×1(front)
Size:(LWD)	188×125×33mm
Weight	542g / 582g (with sun shade)

ACCESSORIES



HDMI

- 2200mAh/7.4V Li-ion battery
- Sun shade
- Bracket
- 12V1.5A DC adapter
- Remote control
- Manual
- HDMI to mini HDMI cable
- Shoe mount (for camera only)